



INTERASSE 12 - FRONTALE 24 x 8 - ALTEZZA MANIGLIA 1050 e 1020						
Catenaccio a leva	HBB min	HBB max	Frontale	Configurazione Asta a leva sinistra	Configurazione Asta a leva destra	F Lunghezza
Misura A	580 mm	1880 - 2280	24 x 8	6-38871-32-L-1	6-38871-32-R-1	1850
	730 mm	2030 - 2900	24 x 8	6-37900-32-L-1	6-37900-32-R-1	2000
	915 mm	2215 - 3115	24 x 8	6-38869-32-L-1	6-38869-32-R-1	2185
<b>Terminale Inferiore</b>						
<b>Altezza maniglia</b>		<b>G 1050 mm</b>	24 x 8	6-39293-32-0-1	6-39293-32-0-1	160
		<b>G 1020 mm</b>	24 x 8	6-35765-01-0-1	6-35765-01-0-1	130
<b>Terminale Superiore</b> (con terminale inferiore da 130 mm sottrarre 30mm da HBB min e HBB max)						
Misura A	580 mm	1880 - 2140	24 x 8	6-35765-01-0-1	6-35765-01-0-1	130
		2141 - 2280	24 x 8	6-35765-41-0-1	6-35765-41-0-1	270
	730 mm	2030 - 2290	24 x 8	6-35765-01-0-1	6-35765-01-0-1	130
		2291 - 2430	24 x 8	6-35765-41-0-1	6-35765-41-0-1	270
		2431 - 2680	24 x 8	6-35765-44-0-1	6-35765-44-0-1	520
		2681 - 2930	24 x 8	6-35765-47-0-1	6-35765-47-0-1	770
	915 mm	2215 - 2475	24 x 8	6-35765-01-0-1	6-35765-01-0-1	130
		2476 - 2615	24 x 8	6-35765-41-0-1	6-35765-41-0-1	270
		2616 - 2865	24 x 8	6-35765-44-0-1	6-35765-44-0-1	520
		2866 - 3115	24 x 8	6-35765-47-0-1	6-35765-47-0-1	770

In questa versione è applicabile l'apriporta elettrico

INTERASSE 12 - FRONTALE 26 x 8 - ALTEZZA MANIGLIA 1050 e 1020						
Catenaccio a leva	HBB min	HBB max	Frontale	Configurazione Asta a leva sinistra	Configurazione Asta a leva destra	F Lunghezza
Misura A	580 mm	1880 - 2280	26 x 8	6-38871-33-L-1	6-38871-33-R-1	1850
	730 mm	2030 - 2900	26 x 8	6-37900-33-L-1	6-37900-33-R-1	2000
	915 mm	2215 - 3115	26 x 8	6-38869-33-L-1	6-38869-33-R-1	2185
<b>Terminale Inferiore</b>						
<b>Altezza maniglia</b>		<b>G 1050 mm</b>	26 x 8	6-39293-33-L-1	6-39293-33-R-1	160
		<b>G 1020 mm</b>	26 x 8	6-35765-13-L-1	6-35765-13-R-1	130
<b>Terminale Superiore</b> (con terminale inferiore da 130 mm sottrarre 30mm da HBB min e HBB max)						
Misura A	580 mm	1880 - 2140	26 x 8	6-35765-13-R-1	6-35765-13-L-1	130
		2141 - 2280	26 x 8	6-35765-53-R-1	6-35765-53-L-1	270
	730 mm	2030 - 2290	26 x 8	6-35765-13-R-1	6-35765-13-L-1	130
		2291 - 2430	26 x 8	6-35765-53-R-1	6-35765-53-L-1	270
		2431 - 2680	26 x 8	6-35765-56-R-1	6-35765-56-L-1	520
		2681 - 2930	26 x 8	6-35765-59-R-1	6-35765-59-L-1	770
	915 mm	2215 - 2475	26 x 8	6-35765-13-R-1	6-35765-13-L-1	130
		2476 - 2615	26 x 8	6-35765-53-R-1	6-35765-53-L-1	270
		2616 - 2865	26 x 8	6-35765-56-R-1	6-35765-56-L-1	520
		2866 - 3115	26 x 8	6-35765-59-R-1	6-35765-59-L-1	770