**UNI-JET M6/12 – hinge-side accessories** 


## **UNI-JET M6/12 – hinge-side accessories**

## Pivot-rest

Pivot-rest / 2 x Ø 34 mm drill-hole part for pivot-rest










Pivot-rest M6/100				
Item	System	PU	Order number	
54F	12/18-9+13	100	6-36876-18-L/R-1	
	12/20-9+13		6-36876-20-L/R-1	
	12/18-9+13		6-36876-84-L/R-1 <sup>[1]</sup>	

- Compatible with hinge-side M6 up to 100 kg sash weight
- Drill-hole part (2 x Ø 34 x 6 mm)
- Version with flush overlap



Pivot-rest M6/130					
Item	System	PU	Order number		
	12/18-9+13		6-36899-18-L/R-1		
54G	12/20-9+13	100	6-36899-20-L/R-1		
	12/18-9+13		6-36899-84-L/R-1 <sup>[1]</sup>		

- Compatible with hinge-side M6 up to 130 kg sash weight
- Drill-hole part (2 x Ø 34 x 6 mm)
- Version with flush overlap





GU



Pivot-rest M6/100 Item System PU Order number 12/18-9+13 6-36875-00-0-1 100 12/20-9+13

- Compatible with hinge-side M6 up to 100 kg sash weight
- For 2-part pivot-rest versions
- Only in conjunction with 2 x Ø 34 mm drill-hole part for M6 pivot-rest 9-37919-□□
- Version with flush overlap



Pivot-rest M6/130				
Item	System	PU	Order number	
54N	12/18-9+13	100	6-36875-01-0-1	
	12/20-9+13			

- Compatible with hinge-side M6 up to 130 kg sash weight
- For 2-part pivot-rest versions
- Only in conjunction with 2 x Ø 34 mm drill-hole part for M6 pivot-rest 9-37919-□□



2 x Ø 34 mm drill-hole part for M6 pivot-rest					
Item	System	PU	Order number		
	12/18-9+13		9-37919-18-0-1		
54M	12/20-9+13	100	9-37919-20-0-1		
	12/18-9+13		9-37919-84-0-1[1]		

- Compatible with hinge-side M6 up to 130 kg sash weight
- For 2-part pivot-rest versions
- Drill-hole part (2 x Ø 34 x 6 mm)
- Only in conjunction with pivot-rest 6-36875-00 (100 kg) or pivot-rest 6-36875-01 (130 kg)
- Version with flush overlap

[1] The drill holes for the 2 additional size 84 pins (8 mm bore hole diameter / length 5 mm) are 21.6 mm apart on the axis of the fixing screws. See installation drawing 0-46605.

[1] The drill holes for the 2 additional size 84 pins (8 mm bore hole diameter / length 5 mm) are 21.6 mm apart on the axis of the fixing screws. See installation drawing 0-46605.