

2 00

Cavo Ømm. 2,00 AISI316 a 19 fili su bobina da mt. 100  
N.B.: Cavo fornito senza terminale saldato. Utilizzare con morsetto MF1002. Portata limitata

Cable Ø mm. 2,00 AISI316 19 wires on spool of mt.100  
N.B.: Cable furnished without welded ending. Use with clip MF1002. Limited capacity




CA200X mt. 100

8032611955860

2 01


Cavo Ømm. 2,00 AISI316 19 fili con cilindro Ø6x3.50 saldato  
Cable Ømm. 2,00 AISI316 19 wires with Ø6x3.50 welded cylinder



CA20005XIB	mt. 0,50	1	8032611953286
CA20005XI	mt. 0,50	12	8032611953279
CA20010XIB	mt. 1,00	1	8032611951008
CA20010XI	mt. 1,00	12	8032611951015
CA20015XIB	mt. 1,50	1	8032611951022
CA20015XI	mt. 1,50	12	8032611951039
CA20020XIB	mt. 2,00	1	8032611951046
CA20020XI	mt. 2,00	12	8032611951053
CA20025XIB	mt. 2,50	1	8032611951060
CA20025XI	mt. 2,50	12	8032611951077
CA20030XIB	mt. 3,00	1	8032611951084
CA20030XI	mt. 3,00	12	8032611951091
CA20035XIB	mt. 3,50	1	8032611951107
CA20035XI	mt. 3,50	12	8032611951114
CA20040XIB	mt. 4,00	1	8032611951121
CA20040XI	mt. 4,00	12	8032611951138
CA20045XIB	mt. 4,50	1	8032611951145
CA20045XI	mt. 4,50	12	8032611951152
CA20050XIB	mt. 5,00	1	8032611951169
CA20050XI	mt. 5,00	12	8032611951176
CA20060XIB	mt. 6,00	1	8032611953231
CA20060XI	mt. 6,00	12	8032611952586

2 02



Cavo Ømm. 1,50 AISI316 49 fili con cilindro Ø5x4.50 pressato per sistema SOLO  
Cable Ømm. 1,50 AISI316 49 wires with Ø5x4.50 pressed cylinder for SOLO system



CA15005XIB	mt. 0,50	10	8032611953446
CA15010XIB	mt. 1,00	10	8032611953453
CA15015XIB	mt. 1,50	10	8032611953460
CA15020XIB	mt. 2,00	10	8032611953095

2 03

Cavo Ømm. 1,50 AISI316 49 fili con cilindro Ø6x3.50 saldato per sistema MOMA  
Cable Ømm. 1,50 AISI316 49 wires with Ø6x3.50 welded cylinder for MOMA system



CA15005XMB	mt. 0,50	10	8032611954016
CA15010XMB	mt. 1,00	10	8032611954023
CA15015XMB	mt. 1,50	10	8032611954030
CA15020XMB	mt. 2,00	10	8032611953101