


SUPPORTI / CASTORS



Medio / Medium duty

Ruota in poliuretano ad iniezione DESMOPAN®, nucleo in poliammide 6 / Injection polyurethane DESMOPAN® wheel tread, polyamide 6 centre



70 ÷ 300

-20 ÷ +80

Supporti tipo medio in acciaio stampato zinco-cromato rotanti su doppia corona di sfere. Assemblaggio con dado autobloccante. Anello parapolvere sul giro di sfere.

Medium duty castors in zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Accessori a richiesta: perni filettati e cilindrici di varie dimensioni. Parapiedi.
On request: threaded pin fitting and round stem fitting with various dimensions. Foot guards.

Le ruote 17G-S e 61 possono essere assemblate con tutti i supporti tipo medio.
Wheels 17G-S and 61 can be assembled with all medium duty castors.



Model	Plate Size	Wheel Size	Wheel Dia	Stem Dia	Stem Length	Stem Dia	Stem Length	Stem Dia	daN Dynamic	daN Static
60x24	100x85	80x60	8,5x12	37	89	87	20x50	12	70	100
80x30	100x85	80x60	8,5x12	37	108	106	20x50	12	120	150
100x30	100x85	80x60	8,5x12	37	128	126	20x50	12	120	150
125SEx35	100x85	80x60	8,5x12	37	154	152	20x50	12	130	170
125x35	100x85	80x60	8,5x12	42	155	150	22x50	12	170	220
125x35	140x110	105x80	11x16	42	155	150	22x50	12	170	220
150SEx40	100x85	80x60	8,5x12	37	179	177	20x50	12	130	170
150x40	100x85	80x60	8,5x12	45	181	178	22x50	12	200	250
150x40	140x110	105x80	11x16	45	181	178	22x50	12	200	250
160x40	140x110	105x80	11x16	55	197	194	22x50	16	300	380
175x45	140x110	105x80	11x16	55	208	205	22x50	16	300	380
200x50	140x110	105x80	11x16	55	235	232	22x50	16	300	380